


# Surface Mount Wall Grazer: HD-W04054WX

## Product Features

LED wall grazer are one of the most popular lighting fixtures for façade lighting projects. They can be used to create a stunning effect on both large and small projects. We offer a wide range of LED wall grazer, from 12 to 100 watts, in a variety of color temperatures, including RGB, single color, and tunable white.



## PHYSICAL

Body	Extruded Aluminium
Dimensions	W95*H95*L1000mm
Finish	Powder Coating
IP Rating	IP67

## OPTICAL

Lamp	LED
Cover	Clear Tempered glass
Beam Angle	8°/10°/15°/45°/60°/80° / 10°30°/20°45°/15°65°/15°45°
Color Temp.	Single Color
LED Chip	CREE   OSRAM
Lumen Output	+85lm / W
Color rendering i(Ra):	>82
Power factor (PF):	>0.9

## ELECTRICAL

Power	36*5W
Controller	Switch   Dali   DMX
Input voltage	100V -240V
Lamp life	50,000 h
Ambient Temp.	-25°C ~ 50°C
Ambient Humidity	-25% ~ +60%
PCB	Excellent heat conductivity aluminum coefficient of heat conductivity ≥ 2.0w/mk
PCB Voltage protection	Reverse voltage protection
PCB Current Stabilization	Integrated current stabilization system

Ref.	Wattage	Voltage	Color Temp	Beam	Control
HD-W04072WX	36*5W	AC220V	Single Color	3°/5°/8°/15°/30°/60° / 10°30°/20°45°/15°65°/15°45°	On/Off
HD-W04048R3	36*6W(3in1)	AC220V	RGB	15°/30°/60°/80° / 15°45°	DMX
HD-W04072R3	72*2W(3in1)	AC220V	RGB	20°/30°/60°/80° / 15°45°	DMX
HD-W04048R4	36*8wW(4in1)	AC220V	RGBW	15°/30°/60°/80° / 15°45°	DMX
HD-W04072R4	72*3W(4in1)	AC220V	RGBW	20°/30°/60°/80° / 15°45°	DMX