

Surface Mount Wall Grazer: HD-W06018WX



Product Features

LED wall grazer are one of the most popular lighting fixtures for façade lighting projects. They can be used to create a stunning effect on both large and small projects. We offer a wide range of LED wall grazer, from 12 to 100 watts, in a variety of color temperatures, including RGB, single color, and tunable white.



PHYSICAL


Body	Extruded Aluminium
Dimensions	W40*H60*L1000mm
Finish	Powdear Coating
IP Rating	IP67

OPTICAL

Lamp	LED
Cover	Clear Tempered glass
Beam Angle	8°/10°/15°/45°/60°/80° / 10°30°/20°45°/15°65°/15°45°
Color Temp.	Single Color
LED Chip	CREE OSRAM
Lumen Output	+85lm / W
Color rendering i(Ra):	>82
Power factor (PF):	>0.9

ELECTRICAL

Power	24W 36W 48W
Controller	Switch Dali DMX
Input voltage	DC24V
Lamp life	50,000 h
Ambient Temp.	-25°C ~ 50°C
Ambient Humidity	-25% ~ +60%
PCB	Excellent heat conductivity aluminum coefficient of heat conductivity ≥ 2.0w/mk
PCB Voltage protection	Reverse voltage protection
PCB Current Stabilization	Integrated current stabilization system



Ref.	Wattage	Voltage	Color Temp	Beam	Control
HD-W06024WX	24*1W	DC24V	Single Color	8°/10°/15°/45°/60°/80° / 10°30°/20°45°/15°65°/15°45°	On/Off
HD-W06036WX	36*1W	DC24V	Single Color	20°/30°/60°/80° / 15°45°	On/Off
HD-W06018R3	18*2W(3in1)	DC24V	RGB	20°/30°/60°/80° / 15°45°	DMX
HD-W06024R3	24*1.5W(3in1)	DC24V	RGB	20°/30°/60°/80° / 15°45°	DMX
HD-W06018R4	18*2W(4in1)	DC24V	RGBW	20°/30°/60°/80° / 15°45°	DMX
HD-W06024R4	24*2W(4in1)	DC24V	RGBW	20°/30°/60°/80° / 15°45°	DMX