Surface Mount Wall Grazer: HD-W08036WX



Product Features

LED wall grazer are one of the most popular lighting fixtures for façade lighting projects. They can be used to create a stunning effect on both large and small projects. We offer a wide range of LED wall grazer, from 12 to 100 watts, in a variety of color temperatures, including RGB, single color, and tunable white.













PHYSICAL

Extruded Aluminium Body Dimensions W34*H65*L1000mm Finish Powdear Coating IP65 **IP** Rating

OPTICAL


LED Lamp

Cover Clear Tempered glass

Beam Angle 8°/10°/15°/45°/60°/80°/ 10*30°/20*45°/15*65°/15*45°

Color Temp. Single Color LED Chip CREE | OSRAM Lumen Output +85lm / W Color rendering i(Ra): >82 Power factor (PF): >0.9





ELECTRICAL

Power 24*1W Controller On/Off Input voltage DC24V Lamp life 50,000 h Ambient Temp. -25°C ~ 50°C **Ambient Humidity** -25% ~ +60% PCB Excellent heat conductivity aluminum

coefficient of heat conductivity ≥ 2.0w/mk

PCB Voltage protection Reverse voltage protection

PCB Current Stabilization Integrated current stabilization system

Ref.	Wattage	Voltage	Color Temp	Beam	Control
HD-W08036WX	36*1W	DC24V	Single Color	8°/10°/15°/45°/60°/80°/ 10*30°/20*45°/15*65°/15*45°	On/Off
HD-W08024R3	24*2(3in1)	DC24V	RGB	8°/10°/15°/45°/60°/80°/ 10*30°/20*45°/15*65°/15*45°	DMX
HD-W08024R4	24*2.5(4in1)	DC24V	RGBW	20°/30°/60°/80°/15*45°	DMX

Hondel Lighting Limited www.hondellighting.com