


LED STRIP LIGHT





LED STRIP LIGHT

WHERE CREATIVITY GLOWS


LED white light consistency

Colour consistency of LED lighting products is an important index of product colour quality, and colour tolerance is an important reference standard to measure this index. Most of LMAN's products adopt third-order colour tolerance, pure light colour, good consistency, and achieve subtle differences that cannot be recognized by human naked eyes.

colour tolerance: It is used to show the accuracy of human eyes' visual differences in colours and distinguish similar colours. It is expressed by the size of elliptical areas, the unit is commonly used in step (SDCM); The smaller the ellipse, the higher the accuracy.



MacAdam 7step, 5step, 3step, 2step, ellipse contrast at 3000K colour temperature
 International requirements: colour tolerance of 7step (SDCM, order)
 EU ERP Directive: colour tolerance 6step (SDCM, order)
 Energy Star ANSI: colour tolerance of 7step (SDCM, order)
 colour tolerance of 3step, the human eye basically can not recognize the colour difference;
 colour tolerance is 5step, and the human eye can recognize it, with a slight colour difference;
 colour tolerance of 7step, the human eye can recognize, the colour difference is very obvious;



High CRI

Colour rendering index is an important method to evaluate the colour rendering of light source, and it is also an important parameter to measure the colour characteristics of artificial light source, which is expressed by Ra/CRI. Usually, the higher the value, the closer the colour of sunlight, and the closer it is to its true colour. In the props industry, LED lighting sources with high colour rendering index are usually selected. The products provided by LMAN usually adopt CRI > 95 according to customer needs, which can truly restore the colour of goods in lighting, so as to achieve pleasing to the eye and stimulate people's desire to buy.



RA > 95/98




RA > 83



RA > 70

Ra与R9、R15

Generally, the colour rendering index Ra is the average of R1 to R8, and the colour rendering index CRI is the average of R1-R14. LMAN not only considers the general colour rendering index Ra, but also pays more attention to the special index R9 for saturation red and the special colour rendering index R9-R12 for saturation colours of red, yellow, green and blue. We think that these indexes truly represent the quality LED light source, while for commercial lighting sources, only when these indexes have high values can the high colour rendering of LED be guaranteed.



R9

R9?

R9 is the colour rendering ability to red, and the larger the value, the higher the reduction of red. Simply put, the higher the lamp R9, the illumination in fruits, flowers and other occasions The effect is even better, even more colourful.




R15

R15?

R15 is the colour rendering ability of oriental women's skin colour. The larger the value, the better the reduction ability of skin colour. It is more important in lighting counters such as cosmetics and clothing.



Explore TM-30 with higher light quality

LMAN In the process of technical communication with North American customers, It is found that they have higher and higher requirements for LED light colour rendering and high-quality light. Therefore, IES of North American Lighting Committee has defined a new evaluation method TM-30 for light source colour rendering ability, and put forward two brand-new test indexes Rf and Rg, which fully shows that international peers are really bringing forth new ideas in LED light research. For LMAN, we quickly introduce this kind of light evaluation method in the industry, so that Chinese people can fully enjoy higher quality LED light sources, thus leading the domestic trend.



TM-30 colourimetric Icon

The TM-30 compares 99 colour samples, representing all the common colours that life can see (from saturated to unsaturated, from light to dark)



LED colour temperature

LED colour temperature is one of the most basic and important technical indexes for rating LED light colour. colour temperature not only affects the colour and senses of irradiated objects, but also often affects human emotions. LED light source in the props industry, no matter the importance of colour temperature is raised to any height, LMAN thinks it is not too much. It is expressed by absolute temperature K, that is, the standard blackbody is heated. When the temperature rises to a certain extent, the colour of the blackbody begins to be deep red-light red-orange-yellow-white-blue, and gradually changes. When the colour of a certain light source is the same as that of the blackbody, we call the absolute temperature of the blackbody as the LED colour temperature of the light source.

3200K



ceramic art



display ladies' perfume



glass ornaments



fashion modern environment space



hardware handicrafts



hardware sanitary ware

4000K



nephrite Jewelry



crystal Jewelry



boys Perfume Counter



Based on the years of experience of LMAN and Marketplace, we recommend some of the most commonly used color temperatures of LED light sources for props, and finally take the customer's naked eye as the standard.

LMAN flexible customization scheme



IPxx



Optional IPxx protection level



CRI




Customizable CRI



Color



Customizable colors



Connection



Customizable special connection structure



BIN



BIN area optional



Length



Customizable length



Label



Customizable label



Packaging



Customizable packaging




Power



Customizable special power



LOW VOLTAGE LED STRIP
DC12V/24V/36V



LED strip

1



LED chip

2




IPxx protection

3



Packaging




paste



radiator



aluminum profile




clip A



clip B

Installation


4




single PIN waterproof docking terminal



2 PIN waterproof docking terminal



the corner connection terminal



double PIN T connector

Connector

5



red and black line



SM male/female head line



DC male/female head silicone line



DC male/female head PVC line

Outlet line

6



DC male/female head crystal line

LLV-2835-60P-ECO/ Economical type



Product features:


Safe, stable circuit scheme
 High quality chip, high brightness high CRI
 Low light decay, with a long life span
 Good flexibility and folding resistance

Scope of application:

Showcase, cabinets, wardrobes, lighting decorations
 Home decoration, shopping malls, hotels, signs,
 entertainment clubs, linear applications.



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-60P-ECO DC12/24V	● 3000K	4.8W	60	480	100	> 93	W8*H3mm
	● 4000K	4.8W	60	530	110	> 93	
	○ 6000K	4.8W	60	580	121	> 93	
	● 1800-10000K	4.8W	60	630	131	> 93	
	● Others	4.8W	60	/	/	/	

LLV-2835-120P-HC/ RA>83/93



Product features:


High CRI, good eye protection
 Low light decay, with a long life span
 Good flexibility and folding resistance

Scope of application:


Showcase, cabinets, wardrobes and other lighting
 decoration
 Museums, libraries and other exhibition hall lighting
 applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-120P-HC DC12/24V	● 3000K	9.6W	120	960	100	> 83/93	W5*H3mm
	● 4000K	9.6W	120	1000	104	> 83/93	
	○ 6000K	9.6W	120	1050	110	> 83/93	
	● 1800-10000K	9.6W	120	1100	115	> 83/93	
	● Others	9.6W	120	/	/	/	

LLV-2835-120P-FS/ RA>96/98



Product features:


High quality chip, full spectrum CRI
 Low light decay, with a long life span
 Good flexibility and folding resistance

Scope of application:

Showcase, cabinets, wardrobes and other lighting decoration
 Museums, libraries and other exhibition hall lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-120P-FS DC12/24V	3000K	11W	120	950	86	>96/98	W10*H3mm
	4000K	11W	120	1000	91	>96/98	
	6000K	11W	120	1050	95	>96/98	
	1800-10000K	11W	120	1100	100	>96/98	
	Others	11W	120	/	/	/	

LLV-2835-120P-PH/ PHILIPS chip



Product features:


Imported brand chip, bright and high CRI
 Low light decay, with a long life span
 Good flexibility and folding resistance

Scope of application:

Showcase, cabinets, wardrobes and other lighting decoration
 High-end engineering villa application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-120P-PH DC12/24V	3000K	11W	120	950	86	>93	W8*H3mm
	4000K	11W	120	1000	91	>93	
	6000K	11W	120	1050	95	>93	
	1800-10000K	11W	120	1100	100	>93	
	Others	11W	120	/	/	/	

LLV-2835-120P-ND/ Non power drop



Product features:


Lighting length reach 35 meters without power drop
 3 oz circuit board, with good electrical conductivity
 Intelligent temperature control IC implantation, high stability circuit

Scope of application:

The 20-30 meters billboard, the background wall lighting application
 Indoor and outdoor long-distance engineering building lighting application



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-120P-ND DC24V	3000K	8W	120	780	98	> 93	W10*H3mm
	4000K	8W	120	830	104	> 93	
	6000K	8W	120	880	110	> 93	
	1800-10000K	8W	120	930	116	> 93	
	Others	8W	120	/	/	/	

LLV-2835-120P-OC/ One led cuttable



Product features:


Limit cutting distance, one chip one cut
 Other linear products can be used at will

Scope of application:

Showcase, wardrobe, accessories cabinet applications
 Ceiling, dark slot special corner application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-120P-OC DC24V	3000K	9.6W	120	960	100	> 93	W5*H3mm
	4000K	9.6W	120	1000	104	> 93	
	6000K	9.6W	120	1050	109	> 93	
	1800-10000K	9.6W	120	1100	115	> 93	
	Others	9.6W	120	/	/	/	

LLV-2835-168P-HB/ High bright



Product features:


Highlight output, stability circuit
Ideal matching line light source for linear lighting

Scope of application:

Interior and outdoor decorative lighting
Aluminum profile, silicone neon and other linear lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-168P-HB DC12/24V	3000K	16W	168	1550	97	>93	W8*H3mm
	4000K	16W	168	1600	100	>93	
	6000K	16W	168	1650	103	>93	
	1800-10000K	16W	168	1700	106	>93	
	Others	16W	168	/	/	/	

LLV-2835-192P-SD/ Super dense chip



Product features:


Encryption to the LED line design
Highlight output, stability circuit
Linear lighting high-quality supporting line light source

Scope of application:

Interior and outdoor decorative lighting
Aluminum profile, silicone neon and other linear lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-192P-SD DC12/24V	3000K	16W	192	1750	110	>93	W8*H3mm W10*H3mm
	4000K	16W	192	1800	113	>93	
	6000K	16W	192	1850	116	>93	
	1800-10000K	16W	192	1900	119	>93	
	Others	16W	192	/	/	/	

LLV-2835-240P-UB/ Ultra bright



Product features:


Super-dense LED line design
 Highlight output, stability circuit
 Excellent matching line light source for linear lighting

Scope of application:

Interior and outdoor decorative lighting
 Aluminum profile, silicone neon and other linear lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-240P-UB DC12/24V	3000K	19.2W	240	2100	110	> 93	W10*H3mm
	4000K	19.2W	240	2150	112	> 93	
	6000K	19.2W	240	2200	115	> 93	
	1800-10000	19.2W	240	2250	117	> 93	
	Others	19.2W	240	/	/	/	

LLV-2835-360P-TL/ 360 LEDES



Product features:


Double-row encrypted line design
 Ultra-high optical flux output

Scope of application:

Interior and outdoor decorative lighting
 Large size aluminum profile, silicone neon and other linear lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-360P-TL DC12/24V	3000K	28.8W	360	3150	110	> 93	W15*H3mm
	4000K	28.8W	360	3200	111	> 93	
	6000K	28.8W	360	3250	113	> 93	
	1800-10000	28.8W	360	3300	115	> 93	
	Others	28.8W	360	/	/	/	

LLV-2025-168P-SN/ 3mm width



Product features:


Utmost narrow, utmost tiny, utmost delicate
Limit space, greater application
No dark area, no light spots

Scope of application:

Interior and outdoor decorative lighting
Aluminum profile, silicone neon and other
linear lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2025-168P-SN DC12/24V	3000K	9W	168	800	89	>93	W3*H3mm
	4000K	9W	168	840	93	>93	
	6000K	9W	168	880	98	>93	
	1800-10000K	9W	168	920	102	>93	
	Others	9W	168	/	/	/	

LLV-2025-280P-DF/ Dots-free



Product features:


The chips are more delicate and shine more closely
The latest matching line light source for linear lighting

Scope of application:

Interior and outdoor decorative lighting
Aluminum profile, silicone neon and other
linear lighting applications



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2025-280P-DF DC12/24V	3000K	10W	280	1020	102	>93	W8*H3mm
	4000K	10W	280	1060	106	>93	
	6000K	10W	280	1100	110	>93	
	1800-10000K	10W	280	1140	114	>93	
	Others	10W	280	/	/	/	

LLV-5050-60P-PQ/ Project quality



Product features:


3-5 years warranty project item
High-quality three-core LED chips
Stable circuit, long life span

Scope of application:

High-end villa engineering, stores, automobile
4S shop and other lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-60P-PQ DC12/24V	● 3000K	14.4W	60	1120	78	>83/90	W10*H3mm
	● 4000K	14.4W	60	1160	81	>83/90	
	○ 6000K	14.4W	60	1200	83	>83/90	
	● 1800-10000K	14.4W	60	1240	86	>83/90	
	● Others	14.4W	60	/	/	/	

LLV-5050-120P-PT/ Project quality



Product features:


3-5 years warranty project item
High-quality three-core LED chips
Double-row high-light scheme design

Scope of application:

High-end villa engineering, stores, automobile
4S shop and other lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-120P-PT DC12/24V	● 3000K	20W	120	1850	92	>93	W15*H3mm
	● 4000K	20W	120	1950	95	>93	
	○ 6000K	20W	120	2000	98	>93	
	● 1800-10000K	20W	120	2050	100	>93	
	● Others	20W	120	/	/	/	

LLV-WW2835-108P/ Indoor wall washer



Product features:


Structural design of bare plate wall washing
Special LED lens principle
Easy to install and easy to use

Scope of application:

Objects, building, building body,
building contour wall washing effect



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-WW2835-108P DC24V	● 3000K	10W	108	1050	100	> 83	W8*H8mm
	● 4000K	10W	108	1100	105	> 83	
	○ 6000K	10W	108	1150	109	> 83	
	● 1800-10000	10W	108	1200	115	> 83	
	● Others	10W	108	/	/	/	





SPECKLE-FREE
COB LED STRIP

—

LLV-COB-320P-ECO/ Economical type



Product features:


Light lowing uniform, good continuity
Soft light is not dazzling
Good folding and bending resistance and flexibility

Scope of application:

Wardrobe, cabinets, display cabinets and other lighting applications
Home decoration, office space decorative lighting



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-320P-ECO DC12/24V	● 3000K	10W	320	850	85	> 93	W8*H3mm
	● 4000K	10W	320	900	90	> 93	
	○ 6000K	10W	320	950	95	> 93	
	● 1800-10000K	10W	320	1000	100	> 93	
	● Others	10W	320	/	/	/	

LLV-COB-420P-HB/ High bright



Product features:


Light lowing uniform, good continuity
Soft light is not dazzling
Good folding and bending resistance and flexibility

Scope of application:

Wardrobe, cabinets, display cabinets and other lighting applications
Home decoration, office space decorative lighting



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-420P-HB DC12/24V	● 3000K	10W	420	950	95	> 93	W8*H3mm
	● 4000K	10W	420	1000	100	> 93	
	○ 6000K	10W	420	1050	105	> 93	
	● 1800-10000K	10W	420	1100	110	> 93	
	● Others	10W	420	/	/	/	

LLV-COB-480P-SB/ Super bright



Product features:


High-density chip implantation design
Light strip soft light is not dazzling
Good folding and bending resistance and flexibility

Scope of application:

Wardrobe, cabinets, display cabinets and other lighting applications
Home decoration, office space decorative lighting



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-480P-SB DC12/24V	● 3000K	10W	480	1050	105	> 93	W10*H3mm
	● 4000K	10W	480	1100	110	> 93	
	○ 6000K	10W	480	1150	115	> 93	
	● 1800-10000K	10W	480	1200	120	> 93	
	● Others	10W	480	/	/	/	

LLV-COB-480P-SN/5mm width



Product features:


5mm plate width and high precision line design
Light strip soft light is not dazzling
Good folding and bending resistance and flexibility

Scope of application:

Utmost narrow and limited-space installation
Wardrobe, cabinets, display cabinets and other lighting applications
Home decoration, office space decorative lighting



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-480P-SN DC12/24V	● 3000K	10W	480	1050	105	> 93	W5*H3mm
	● 4000K	10W	480	1100	110	> 93	
	○ 6000K	10W	480	1150	115	> 93	
	● 1800-10000K	10W	480	1200	120	> 93	
	● Others	10W	480	/	/	/	

LPHV-COB-288P- 220V/ High voltage type



Product features:


With 30-50 meters of light length
IP65 outdoor waterproof grade

Scope of application:

Interior and outdoor decorative lighting
Ceiling, dark groove, outline decoration lighting



Product Size



Applicable scenarios




Product parameters


Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-COB-288P-110V/220V	● 3000K	10W	288	750	75	> 83	W14*H6mm
	● 4000K	10W	288	800	80	> 83	
	○ 6000K	10W	288	850	85	> 83	
	● 1800-10000K	10W	288	900	90	> 83	
	● Others	10W	288	/	/	/	



NEON FLEX ROPE LIGHT



—





Connect caps

1




Fitting of accessories

3

Connector

4




Packaging

5



LED chip

2



LSNF-0613-AS/ Ad words and signs



Product features:


- Mini-size, soft and curved
- Advertising light word preferred products
- Short shear distance, easy modeling
- Pure silicone extrusion tech

Scope of application:

Indoor and outdoor advertising words, luminous words, contour modeling and other applications



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSNF-0613-AS DC24V	3000K	10W	120	650	65	>83	W6*H13mm
	4000K	10W	120	700	70	>83	
	6000K	10W	120	750	75	>83	
	1800-10000K	10W	120	800	80	>83	
	Others	10W	120	/	/	/	

LSNF-1005-SS/ Silicone smooth



Product features:


- Positive curved top luminous
- Soft light and not dazzling
- Soft silicone, easy to bend
- Pure silicone extrusion tech

Scope of application:


Indoor and outdoor scene decoration, contour modeling application



Product Size




Top bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSNF-1005-SS DC24V	3000K	10W	120	650	65	>83	W10*H5mm
	4000K	10W	120	700	70	>83	
	6000K	10W	120	750	75	>83	
	1800-10000K	10W	120	800	80	>83	
	Others	10W	120	/	/	/	

LSNF-1010-SS/Small size



Product features:


- Square plane luminous surface
- Soft silicone, easy to bend
- Soft light and not dazzling
- Pure silicone extrusion tech

Scope of application:


Indoor and outdoor scene decoration, contour modeling application



Product Size



Top bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSNF-1010-SS DC24V	● 3000K	10W	120	650	65	> 83	W10*H10mm
	● 4000K	10W	120	700	70	> 83	
	○ 6000K	10W	120	750	75	> 83	
	● 1800-10000K	10W	120	800	80	> 83	
	● Others	10W	120	/	/	/	

LSNF-1212-MS/ Middle size



Product features:


- Square plane luminous surface
- Soft silicone, easy to bend
- Soft light and not dazzling
- Pure silicone extrusion tech

Scope of application:


Indoor and outdoor scene decoration, contour modeling application



Product Size



Top bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSNF-1212-MS DC24V	● 3000K	10W	120	650	65	> 83	W12*H12mm
	● 4000K	10W	120	700	70	> 83	
	○ 6000K	10W	120	750	75	> 83	
	● 1800-10000K	10W	120	800	80	> 83	
	● Others	10W	120	/	/	/	

LSNF-1616-LS/ Large size



Product features:


Square plane luminous surface
Soft silicone, easy to bend
Soft light and not dazzling
Pure silicone extrusion tech

Scope of application:


Indoor and outdoor scene decoration,
contour modeling application



Product Size




Top bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSNF-1616-LS 24V/220V	● 3000K	10W	120	650	65	> 83	W16*H16mm
	● 4000K	10W	120	700	70	> 83	
	○ 6000K	10W	120	750	75	> 83	
	● 1800-10000K	10W	120	800	80	> 83	
	● Others	10W	120	/	/	/	

LPNF-1016-MS/ Mini size PVC



Product features:


Soft light and not dazzling
Light up to a length of up to 30-50 meters
Outdoor IP65 rain proof grade

Scope of application:


Indoor and outdoor scene decoration,
contour modeling application



Product Size



Side bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-1016-MS 220V	● 3000K	8W	120	650	81	> 83	W10*H16mm
	● 4000K	8W	120	700	87	> 83	
	○ 6000K	8W	120	750	94	> 83	
	● 1800-10000K	8W	120	800	100	> 83	
	● Others	8W	120	/	/	/	

LPNF-1220-WP/ IP67 Waterproof




Product features:


Low voltage input, short shear distance
Outdoor IP67 waterproof grade
Soft side bending performance

Scope of application:


Indoor and outdoor scene decoration, contour modeling application
Hollow, embedded and other scenario applications
Low voltage input, short shear distance



Product Size



Side bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-1220-WP DC24V	3000K	9.6W	120	750	78	> 83	W12*H20mm
	4000K	9.6W	120	800	83	> 83	
	6000K	9.6W	120	850	89	> 83	
	1800-10000K	9.6W	120	900	94	> 83	
	Others	9.6W	120	/	/	/	

LPNF-1616-SF/ Square flat PVC



Product features:


Fashion square graphic design
Uniform luminous and good color fineness of light
Soft light eye protection

Scope of application:


Indoor and outdoor scene decoration, contour modeling application
Hollow, embedded and other scenario applications



Product Size



Top bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-1616-SF 220V	3000K	8W	120	650	81	> 83	W16*H16mm
	4000K	8W	120	700	87	> 83	
	6000K	8W	120	750	94	> 83	
	1800-10000K	8W	120	800	100	> 83	
	Others	8W	120	/	/	/	

LPNF-1525-OD/ Outline decorate PVC



Product features:


Large size, large luminous surface
Soft light and not dazzling
Outdoor waterproof, long-distance application

Scope of application:


Indoor and outdoor scene decoration,
contour modeling application



Product Size




Side bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-1525-OD 220V	3000K	8W	120	650	65	> 83	W15*H25mm
	4000K	8W	120	700	70	> 83	
	6000K	8W	120	750	75	> 83	
	1800-10000K	8W	120	800	80	> 83	
	Others	8W	120	/	/	/	

LPNF-1525-RGB/ Color changing




Product features:


Large size, large luminous surface
Soft light and not dazzling
Outdoor waterproof, long-distance application

Scope of application:


Indoor and outdoor scene decoration,
contour modeling application



Product Size




Side bend



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-1525-RGB 220V	RGB	12W	120	/	/	/	W15*H25mm
	RGB	12W	120	/	/	/	
	RGB	12W	120	/	/	/	
	RGB	12W	120	/	/	/	
	RGB	12W	120	/	/	/	

LPNF-15D/ 360 degree emitting



Product features:


- luminous design
- Omni-directional luminous surface
- Outdoor waterproof, long-distance application

Scope of application:

- Indoor and outdoor scene decoration,
- contour modeling application



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPNF-15D 220V	● 3000K	8W	120	650	81	>83	Φ15mm
	● 4000K	8W	120	700	87	>83	
	○ 6000K	8W	120	750	94	>83	
	● 1800-10000K	8W	120	800	100	>83	
	● Others	8W	120	/	/	/	





SILICONE EXTRUSION
LED STRIP

LSLV-2835-120P-IP65/ Rainproof type



Product features:


Empty injection molding in silicone
Outdoor IP65 rain proof grade
Cold and heat resistance, acid and alkali resistance
Pure silicone extrusion tech

Scope of application:

Outdoor decorative lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-2835-120P-IP65 DC24V	● 3000K	9.6W	120	950	100	>83	W12*H4.5mm
	● 4000K	9.6W	120	1000	105	>83	
	○ 6000K	9.6W	120	1050	109	>83	
	● 1800-10000K	9.6W	120	1100	115	>83	
	● Others	9.6W	120	/	/	/	

LSLV-2835-120P-IP67/ Waterproof type



Product features:


Silicone solid core injection molding
Outdoor IP67 waterproof grade
Food-grade silicone, anti-UV
Pure silicone extrusion tech

Scope of application:

Outdoor decorative lighting applications
Pool, hot spring, bathroom and other water environment applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-2835-120P-IP67 DC24V	● 3000K	9.6W	120	950	100	>83	W12*H4.5mm
	● 4000K	9.6W	120	1000	105	>83	
	○ 6000K	9.6W	120	1050	109	>83	
	● 1800-10000K	9.6W	120	1100	115	>83	
	● Others	9.6W	120	/	/	/	

LSLV-5050-60P-IP67/ Waterproof type



Product features:


Silicone solid core injection molding
Outdoor IP67 waterproof grade
Food-grade silicone, anti-UV
Pure silicone extrusion tech

Scope of application:

Pool, hot spring, bathroom and other water environment applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-5050-60P-IP67 DC24V	● 3000K	10W	60	850	100	> 83	W12*H4.5mm
	● 4000K	10W	60	900	105	> 83	
	○ 6000K	10W	60	950	109	> 83	
	● 1800-10000	10W	60	1000	115	> 83	
	● Others	10W	60	/	/	/	

LSHV-2835-110P-IP67/ AC220V waterproof



Product features:


AC220V input, available for 30-50m
Silicone solid core injection molding
Outdoor IP67 waterproof grade
Pure silicone extrusion tech

Scope of application:

Outdoor decorative lighting applications
Construction, mine and other large construction site lighting application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSHV-2835-110P-IP67 AC220V	● 3000K	7.5W	110	680	90	> 83	W12*H4.5mm
	● 4000K	7.5W	110	730	97	> 83	
	○ 6000K	7.5W	110	780	104	> 83	
	● 1800-10000	7.5W	110	830	115	> 83	
	● Others	7.5W	110	/	/	/	

LSHV-2835-120P-ERP/ High light efficiency



Product features:


100-110lm/W high light efficiency scheme
 Intelligent temperature control IC circuit design
 AC220V input, available for 50-80m
 Outdoor IP67 waterproof grade
 Pure silicone extrusion tech

Scope of application:

Outdoor decorative lighting applications
 Construction, mine and other large construction site lighting application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSHV-2835-120P-ERP AC220V	● 3000K	12W	120	1150	96	> 83	W12*H4.5mm
	● 4000K	12W	120	1200	100	> 83	
	○ 6000K	12W	120	1250	104	> 83	
	● 1800-10000	12W	120	1300	108	> 83	
	● Others	12W	120	/	/	/	

LSHV-2835-144P-ERP/ High light efficiency




Product features:


100-110lm/W high light efficiency scheme
 Intelligent temperature control IC circuit design
 AC220V input, available for 50-80m
 Outdoor IP67 waterproof grade
 Pure silicone extrusion tech

Scope of application:

Outdoor decorative lighting applications
 Construction, mine and other large construction site lighting application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSHV-2835-144P-ERP AC220V	● 3000K	14W	144	1350	96	> 83	W14*H5mm
	● 4000K	14W	144	1400	100	> 83	
	○ 6000K	14W	144	1450	103	> 83	
	● 1800-10000	14W	144	1500	107	> 83	
	● Others	14W	144	/	/	/	

SILICONE FLEXIBLE WALL WASHER

—



LSLV-WW2835-108P/ Indoor wall washer



Product features:


Structural design of bare plate wall washing
 Special LED lens principle
 Easy to install and easy to use

Scope of application:

Objects, building, building body,
 building contour wall washing effect



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-WW2835-108P DC24V	3000K	10W	108	1050	100	> 83	W8*H8mm
	4000K	10W	108	1100	105	> 83	
	6000K	10W	108	1150	109	> 83	
	1800-10000	10W	108	1200	115	> 83	
	Others	10W	108	/	/	/	

LSLV-WW1616-TE/ Top emitting wall washer




Product features:


Flexible, waterproof structure design
 3-5 m flood wall washing height
 Patent certified products

Scope of application:

Building body, building outline
 wall washing effect



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-WW1616-TE DC24V	3000K	19W	192	2150	113	> 83	W16*H16mm
	4000K	19W	192	2200	116	> 83	
	6000K	19W	192	2250	118	> 83	
	1800-10000	19W	192	2300	121	> 83	
	Others	19W	192	/	/	/	

LSLV-WW1616-SE/ Side emitting wall washer



Product features:


Flexible, waterproof structure design
High-density polarizing wall washing effect
Patent certified products

Scope of application:

Building body, building outline
wall washing effect



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LSLV-WW1616-SE DC24V	● 3000K	12W	144	1650	138	> 83	W16*H16mm
	● 4000K	12W	144	1700	142	> 83	
	○ 6000K	12W	144	1750	146	> 83	
	● 1800-10000	12W	144	1800	150	> 83	
	● Others	12W	144	/	/	/	







HIGH VOLTAGE
LED STRIP

AC110V/220V


—




Accessories




8A/10A/12A/15A Power supply




Front connect wire




Middle connect wire




RGB remote controller




RGB key controller




T shape connector




Long middle connector




Long middle connector




Corner connector




Short middle connector




Connect pin



Mounting clips



360 Neon rope mounting clips




End cap


LED chip



AC220V LED strip



50m/100m per roll



complete packaging

Connector



Mounting clips



Packaging



LPHV-2835-120P-ECO/ Economic type



Product features:


Economic sales, excellent quality
Stable performance, worry-free after sale

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-120P-ECO AC110/220V	● 3000K	6W	120	450	75	> 83	W12*H6.8mm
	● 4000K	6W	120	480	80	> 83	
	○ 6000K	6W	120	510	85	> 83	
	● 1800-10000K	6W	120	540	90	> 83	
	● Others	6W	120	/	/	/	

LPHV-2835-120P-EP/ Easy plug




Product features:

Card buckle type installation, convenient and fast
high permeability plastic surface and good color rendering
Stable quality, long life span


Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Snap-on plug

Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-120P-EP AC110/220V	● 3000K	9W	120	800	88	> 83	W14*H6mm
	● 4000K	9W	120	830	92	> 83	
	○ 6000K	9W	120	860	95	> 83	
	● 1800-10000K	9W	120	890	98	> 83	
	● Others	9W	120	/	/	/	

LPHV-2835-180P-EP/ Easy plug



Product features:

Card buckle type installation, convenient and fast
high brightness, large luminous surface
Stable quality, long life span


Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Snap-on plug

Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-180P-EP AC110/220V	● 3000K	11W	180	1000	90	> 83	W14.5*H7mm
	● 4000K	11W	180	1030	93	> 83	
	○ 6000K	11W	180	1060	96	> 83	
	● 1800-10000K	11W	180	1090	99	> 83	
	● Others	11W	180	/	/	/	

LPHV-2835-120P-PF/ Plug free



Product features:


Ultra thin ultra narrow size
Very short cutting distance at 10cm
High voltage plug free
Installation and use of limit space

Scope of application:

Very narrow and limited-space installation
Wardrobe, cabinets, display cabinets and
other lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-120P-PF AC110/220V	● 3000K	9W	120	800	88	> 83	W10*H3mm
	● 4000K	9W	120	830	92	> 83	
	○ 6000K	9W	120	860	95	> 83	
	● 1800-10000K	9W	120	890	98	> 83	
	● Others	9W	120	/	/	/	

LPHV-2835-100P-SC/10cm cuttable



Product features:


Very short cutting distance at 10cm
Meet special length requirements
Plug-free, easy to install

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall special length application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-100P-SC AC110/220V	3000K	7.5W	100	680	90	> 83	W16.5*H8mm
	4000K	7.5W	100	710	94	> 83	
	6000K	7.5W	100	740	98	> 83	
	1800-10000K	7.5W	100	770	102	> 83	
	Others	7.5W	100	/	/	/	

LPHV-2835-144P-HB/ High bright



Product features:


European ERP energy efficiency standards
100-105 lm/W high light efficiency
Stable highlighting design

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall special length application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-144P-HB AC110/220V	3000K	10W	144	1000	100	> 83	W16.5*H8mm
	4000K	10W	144	1020	102	> 83	
	6000K	10W	144	1040	104	> 83	
	1800-10000K	10W	144	1060	106	> 83	
	Others	10W	144	/	/	/	

LPHV-2835-144P-PQ/ Project quality



Product features:


Pressure stabilizing diode circuit design
High-end engineering configuration
Good quality, with a long life span

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-144P-PQ AC110/220V	● 3000K	10W	144	920	92	> 83	W16.5*H8mm
	● 4000K	10W	144	950	95	> 83	
	○ 6000K	10W	144	980	98	> 83	
	● 1800-10000K	10W	144	1010	101	> 83	
	● Others	10W	144	/	/	/	

LPHV-2835-144P-CC/ CCT changeable



Product features:


One chip trichromatic temperature
Atmosphere switching function
Optical stripe anti-glare

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-144P-CC AC110/220V	● 3000K	13W	144	950	73	> 83	W16*H8mm
	● 4000K	13W	144	980	75	> 83	
	○ 6000K	13W	144	1010	77	> 83	
	● 1800-10000K	13W	144	1040	80	> 83	
	● Others	13W	144	/	/	/	

LPHV-2835-180P-DR/ High bright



Product features:


Classic double row design
 Highlight, high CRI, high quality LED
 Outdoor waterproof, 30-50 meters lighting distance

Scope of application:

Indoor and outdoor decorative lighting applications
 Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-180P-DR AC110/220V	● 3000K	11W	180	1050	95	> 83	W18*H8mm
	● 4000K	11W	180	1080	98	> 83	
	○ 6000K	11W	180	1110	100	> 83	
	● 1800-10000K	11W	180	1140	103	> 83	
	● Others	11W	180	/	/	/	

LPHV-2835-180P-TR/ High bright




Product features:


Fashion three-inclined row design
 Highlight, high CRI, high quality LED
 Outdoor waterproof, 30-50 meters lighting distance

Scope of application:

Indoor and outdoor decorative lighting applications
 Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
PHV-2835-180P-TR AC110/220V	● 3000K	11W	180	1050	95	> 83	W18*H8mm
	● 4000K	11W	180	1080	98	> 83	
	○ 6000K	11W	180	1110	100	> 83	
	● 1800-10000K	11W	180	1140	103	> 83	
	● Others	11W	180	/	/	/	

LPHV-2835-240P-SB/ Super bright



Product features:


Encrypted three-row design
Low light decay, high light flux
Alternative products of traditional optical tube

Scope of application:

Indoor and outdoor decorative lighting applications
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-240P-SB AC110/220V	● 3000K	14W	240	1350	96	> 83	W18*H8mm
	● 4000K	14W	240	1380	98	> 83	
	○ 6000K	14W	240	1410	100	> 83	
	● 1800-10000K	14W	240	1440	102	> 83	
	● Others	14W	240	/	/	/	

LPHV-5050-60P-PQ/ Project quality



Product features:


5050 three-chips LED
Stable and mature circuit scheme
Three-year warranty, long life span

Scope of application:

Application of interior and exterior engineering
decoration lighting
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-5050-60P-PQ AC110/220V	● 3000K	8.5W	60	780	91	> 83	W14.5*H8mm
	● 4000K	8.5W	60	810	95	> 83	
	○ 6000K	8.5W	60	840	98	> 83	
	● 1800-10000K	8.5W	60	870	102	> 83	
	● Others	8.5W	60	/	/	/	

LPHV-5050-60P-RGB / Colors changeable type



Product features:


High-quality 5050 RGB chip
Full color change effect
Atmosphere builder

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-5050-60P-RGB AC110/220V	RGB	12W	60	/	/	/	W16.5*H8mm
	RGB	12W	60	/	/	/	
	RGB	12W	60	/	/	/	
	RGB	12W	60	/	/	/	
	RGB	12W	60	/	/	/	

LPHV-5050-120P-RGB/ Colors changeable




Product features:


Double-row encrypted PCB design
High-quality 5050 RGB chip
Full color change effect

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-5050-120P-RGB AC110/220V	RGB	16W	120	/	/	/	W18*H8mm
	RGB	16W	120	/	/	/	
	RGB	16W	120	/	/	/	
	RGB	16W	120	/	/	/	
	RGB	16W	120	/	/	/	

LPHV-5730-180P-SB/ Super bright



Product features:


Double-row large chip design
Large luminous surface, high light flux
High quality 5730 large LED chip

Scope of application:

Application of interior and exterior engineering
decoration lighting
Ceiling, dark slot, background wall application



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-5730-180P-SB AC110/220V	● 3000K	12W	180	1200	100	> 83	W18*H8mm
	● 4000K	12W	180	1230	102	> 83	
	○ 6000K	12W	180	1260	105	> 83	
	● 1800-10000K	12W	180	1290	107	> 83	
	● Others	12W	180	/	/	/	

LPHV-5050-72P-CW/ Construction sites work light



Product features:

The longest supply is 200 meters
High-stability circuit scheme design
Portable, reusable drum design
Plug-free design

Scope of application:


Construction sites work light, industrial and
mining lighting, movable lighting



Male-female connection

Fuse design

Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-5050-72P-CW AC110/220V	● 3000K	8W	72	650	81	> 83	W18*H8mm
	● 4000K	8W	72	680	85	> 83	
	○ 6000K	8W	72	710	88	> 83	
	● 1800-10000K	8W	72	740	92	> 83	
	● Others	8W	72	/	/	/	

LPHV-2835-180P-CW/ Construction sites work light



Product features:

- High brightness output
- High-stability circuit scheme design
- Portable, reusable drum design
- Plug and plug-free design optional


Scope of application:

Construction sites work light, industrial and mining lighting, movable lighting



Male-female connection

Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-180P-CW AC110/220V	3000K	12W	180	1050	87	> 83	W18*H8mm
	4000K	12W	180	1100	92	> 83	
	6000K	12W	180	1150	96	> 83	
	1800-10000K	12W	180	1200	100	> 83	
	Others	12W	180	/	/	/	

LPHV-2835-60/120P DE/ Double emitting




Product features:


- Double sides luminous
- Special circuit design scheme
- High permeability, high brightness

Scope of application:

Construction site engineering application
Indoor and outdoor advertising lighting applications



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LPHV-2835-60P DE LPHV-2835-120P DE AC110/220V	3000K	10W	120	850	85	> 83	W14.5*H8mm
	4000K	10W	120	980	90	> 83	
	6000K	10W	120	1010	95	> 83	
	1800-10000K	10W	120	1040	100	> 83	
	Others	10W	120	/	/	/	

INTELLIGENT LED STRIP



LLV-2835-192P-CC/ CCT changeable



Product features:


The 3000K / 4000K / 6000K is optional
Intelligent three-color dimming control
Home atmosphere creation

Scope of application:

Display cases, cabinets, wardrobes and other decorative lighting
Home decoration, shopping malls, hotels and other linear



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2835-192P-CC DC12/24V	● 3000K	16W	192	1750	109	> 83/90	W8*H3mm
	● 4000K	16W	192	1800	113	> 83/90	
	○ 6000K	16W	192	1850	116	> 83/90	
	● 1800-10000	16W	192	1900	119	> 83/90	
	● Others	16W	192	/	/	/	

LLV-2025-240P-CC/ CCT changeable



Product features:


The 3000K / 4000K / 6000K is optional
Intelligent three-color dimming control
Home atmosphere creation

Scope of application:

Display cases, cabinets, wardrobes and other decorative lighting
Home decoration, shopping malls, hotels and other linear



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-2025-240P-CC DC12/24V	● 3000K	10W	240	1050	105	> 83/90	W5*H3mm
	● 4000K	10W	240	1100	110	> 83/90	
	○ 6000K	10W	240	1150	115	> 83/90	
	● 1800-10000	10W	240	1200	120	> 83/90	
	● Others	10W	240	/	/	/	

LLV-5050-60P-RGB/ Colors changeable




Product features:


RGB seven-color light change
High quality 5050 RGB three-chip
A variety of intelligent control methods

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-60P-RGB DC12/24V	RGB	16W	60	/	/	/	W10*H3mm
	RGB	16W	60	/	/	/	
	RGB	16W	60	/	/	/	
	RGB	16W	60	/	/	/	
	RGB	16W	60	/	/	/	

LLV-5050-60P-RGBW/ 4 in 1 LED



Product features:


RGB + CCT color selection
Four-in-one intelligent LED
Color monochrome intelligent selection

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-60P-RGBW DC12/24V	3000K	20W	60	/	/	/	W12*H3mm
	4000K	20W	60	/	/	/	
	6000K	20W	60	/	/	/	
	1800-10000	20W	60	/	/	/	
	Others	20W	60	/	/	/	

LLV-5050-60P-RGBCW/ 5 in 1 LED



Product features:


- CCT+ RGB + CCT color selection
- Five-in-one intelligent LED
- Color monochrome intelligent selection

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-60P-RGBCW DC12/24V	RGBCW	25W	60	/	/	/	W12*H3mm
	RGBCW	25W	60	/	/	/	
	RGBCW	25W	60	/	/	/	
	RGBCW	25W	60	/	/	/	
	RGBCW	25W	60	/	/	/	

LLV-5050-60P-SF/ Smart flowing effect



Product features:


- Running water chasing effect
- Intelligent IC chip
- Creation of indoor sense of science and technology

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size




Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-5050-60P-RW DC12/24V	3000K	14.4W	60	780	54	83	W10*H3mm
	4000K	14.4W	60	810	56	83	
	6000K	14.4W	60	840	58	83	
	1800-10000	14.4W	60	870	60	83	
	Others	14.4W	60	/	/	/	

LLV-COB-640P-RGB/ Colors changeable




Product features:


Encryption RGB chip design
Colorful change of light without dark area

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-640P-RGB DC12/24V	RGB	14.4W	640	/	/	/	W10*H3mm
	RGB	14.4W	640	/	/	/	
	RGB	14.4W	640	/	/	/	
	RGB	14.4W	640	/	/	/	
	RGB	14.4W	640	/	/	/	

LLV-COB-630P-MC/ Multi-color changeable



Product features:


Traceless magic effect
DMX512 system support
Intelligent switching, intelligent atmosphere creation

Scope of application:

Indoor and outdoor atmosphere decoration application
KTV, bar, gym, cinema and other entertainment venues



Product Size



Applicable scenarios



Product parameters

Model /voltage(V)	CCT(K/nm)	Power(W/m)	LED qty(pcs/m)	Lux(lm/m)	Light effect (lm/W)	CRI(Ra)	Lamp Size(mm)
LLV-COB-630P-MC DC12/24V	Multi color	12W	630	/	/	/	W12*H3mm
	Multi color	12W	630	/	/	/	
	Multi color	12W	630	/	/	/	
	Multi color	12W	630	/	/	/	
	Multi color	12W	630	/	/	/	

ALUMINUM PROFILE

Field of application

Cooperate with the linear lighting products
Interior and outdoor decoration and other lighting project application


Characteristics

With ultra high density, light weight, corrosion resistance
Good thermal conductivity and electrical conductivity
Complete product specifications optional






Product parameters




Model: LAP-3626

Size: 36x26mm



Model: LAP-3660

Size: 36x60mm




Model: LAP-4233


Size: 42x33mm




Product parameters



Model: LAP-5036
Size: 50X36mm




Model: LAP-8016
Size: 80X16mm




Model: LAP-10068
Size: 100X68mm


Product parameters



Model: LAP-20
Size: ϕ 20mm




Model: LAP-1010B
Size: 10X10mm




Model: LAP-1616
Size: 16X16mm




Product parameters



Model: LAP-1713
Size: 17x13mm




Model: LAP-1814
Size: 18X14mm




Model: LAP-2010B
Size: 20X10mm


Product parameters



Model: LAP-2409
Size: 24X09mm



Model: LAP-3020
Size: 30X20mm



Model: LAP-5313
Size: 53X13mm